

Sika Limited

SITE APPLICATION RECORD

Week Commencing:

— / — / —

SITE LOG	AM Measurements	PM Measurements
WEATHER CONDITIONS		
AMBIENT TEMP °C		
SUBSTRATE TEMP °C		
DEW POINT TEMP °C		
RELATIVE HUMIDITY %		
RELATIVE HUMIDITY % WET BULB		
RELATIVE HUMIDITY % DRY BULB		
TIME CLEANER 205 APPLIED		
TIME SIKATAK PRIMER APPLIED TO RAIL		
TIME SIKATAK PRIMER APPLIED TO PANEL		
DOUBLE SIDED TAPE APPLIED		
TIME SIKATAK PANEL ADHESIVE APPLIED		
TIME CLADDING PANELS APPLIED		
No. OF PANELS FIXED		
LOCATION OF AREA FIXED [Grid Line]		
COMMENTS		
SIGNATURE CONTRACTOR REPRESENTATIVE		
SIGNATURE SIKA REPRESENTATIVE		



This has been prepared based on Sika's current knowledge and experience of Sika's products when properly stored, handled and applied under normal conditions. It only applies to the application and product referred to in this report. In case of changes in the parameters of the application, such as changes in substrates etc, or in case of a different application, consult Sika's Technical Service prior to using Sika's products. The user of the product must test the product's suitability for the intended application and purpose. Consult the current technical data sheet. Except as expressly stated in writing Sika's warranty is governed exclusively by our current Standard Terms and Conditions of Sale. In particular, Sika does not warrant the correct application of its products.

Sika Limited, Watchmead, Welwyn Garden City, Herts, AL7 1BQ
Tel: 01707 394444, Fax: 01707 329129, www.sika.co.uk



Registered in England: Number 226822